

DEFY XTREME OPEN

Caliber	<p>El Primero 4021 SX Automatic Chronograph movement with harmonic plate 13^{'''} caliber. Diameter 30 mm. Height : 7.75 mm. 248 components Chronograph bridge, balance & pallet cocks in shock-absorbing Zenithium Z⁺ Incabloc[®] anti-shock device 36'000 vibrations per hour Power reserve over 50 hours 39 jewels Measures short time intervals to a 10th of a second Automatic winding in both directions Central rotor on ball bearings Heavy Metal oscillating weight with carbon fiber inserts</p>
Functions	<p>Hours and minutes in the center Small seconds-hand at 9 o'clock with a 3-branched hand Power reserve indicator from hour axis Central seconds-hand 30-minute counter at 3 o'clock</p>
Case	<p>Black Titanium case. Diameter: 46.5 mm Black Titanium screw-in push-buttons with carbon fiber guilloché patterns Black Titanium screw-in crown with specific protecting device Graduated unidirectional rotating bezel in Black Titanium, with stainless steel decorative screw-heads & satin-finished titanium cone-shaped indexes Helium valve at 10 o'clock Black Titanium screw-in case back with carbon fiber guilloché pattern Water-resistance up to 1'000 meters</p>
Dial	<p>Multi-layered see-through structure composed of shock-resistant transparent Hesalite glass, Carbon fiber layer and silver-coated dial flange 9-branched silvered propeller-shaped bridge revealing heart of 4021 SX El Primero caliber</p>
Crystal	<p>Sapphire glass, 3.8 mm thick, with anti-reflective coating on both sides</p>
Hands	<p>Rhodium-plated luminous hands with red Superluminova inserts Hour & minute "skeleton" rhodium hands</p>
Bracelet	<p>High-temperature resistant bracelet in brushed stainless steel. Kevlar[®] lateral inserts and central links made of carbon fiber & composite alloys, with brushed stainless steel triple folded clasp</p>